

4-10-00

PTO/SB/05 MODIFIED BY AT&amp;T CORP.

## UTILITY

Attorney Docket No.

1999-0727

Total Pages

38

PATENT APPLICATION  
TRANSMITTAL

First Named Inventor or Application Identifier

Aviel D. Rubin

Express Mail Label No.

EL354902593US

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Assistant Commissioner for Patents  
Box Patent Application  
Washington, D.C. 20231

1. ☒ Fee Transmittal Form  
(submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages 23]  
(preferred arrangement set forth below)
- Descriptive title of invention
  - Cross References to Related Applications
  - Statement Regarding Fed sponsored R&D
  - Reference to Microfiche Appendix
  - Background of the Invention
  - Brief Summary of the Invention
  - Brief Description of the Drawings (if filed)
  - Detailed Description
  - Claim(s)
  - Abstract of the Disclosure
3. ☒ Drawing(s) 35 USC 113 [Total Sheets 4]
4. ☒ Oath or Declaration [Total Pages 2]
- a. ☐ Newly executed (original or copy)
  - b. ☐ Copy from a prior application (37 CFR 1.63(d))  
(for continuation/divisional with Box 15 completed)  
[Note Box 15 below]
  - i. ☐ DELETION OF INVENTOR(S)  
Signed statement attached deleting inventor(s)  
named in the prior application, see 37 CFR  
1.63(d)(2) and 1.33(b)

5. ☐ Microfiche Computer Program (Appendix)
6. ☐ Nucleotide and/or Amino Acid Sequence Submission  
(if applicable, all necessary)
- a. ☐ Computer Readable Copy
  - b. ☐ Paper Copy (identical to computer copy)
  - c. ☐ Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

7. ☒ Assignment Papers (cover sheet & document(s))
8. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
9. ☐ English Translation Document (if applicable)
10. ☒ Information Disclosure ☐ Copies of IDS  
Statement (IDS)/PTO-1449 Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)  
(Should be specifically itemized)
13. ☐ Certified Copy of Priority Document(s)  
(if foreign priority is claimed)
14. ☐ Other :

15. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior Application No:

Prior application information: Examiner:

Group/Art Unit:

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

## 16. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label

(Insert Customer No. or Attach bar code label here)

or ☒ Correspondence address below

NAME Samuel H. Dworetzky

ADDRESS AT&amp;T CORP. P.O. Box 4110

CITY Middletown

STATE

New Jersey

ZIP CODE

07748-4110

COUNTRY United States of America

FAX

732-368-6932

## 17. SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED

NAME Benjamin S. Lee

Reg. # 42787

TELEPHONE 973-360-8117

SIGNATURE

DATE 4/7/2000

"Express Mail" Mailing Label Number EL354902593US

Date of Deposit

I hereby certify that this application is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington D.C., 20231

Antoinette Dozier

(Printed Name of Person Mailing Paper)

Antoinette Dozier

(Signature of Person Mailing Paper)



04/07/00

**PATENT APPLICATION**  
**FOR**  
**BROADBAND CERTIFIED MAIL**

Inventors:

**Aviel D. Rubin**, a citizen of United States of America,  
residing at 1 Rubino Road, W Caldwell, New Jersey 07006.

Assignee:

**AT&T CORP.**  
32 Avenue of the Americas  
New York, New York 10013-2412  
A New York Corporation.

Entity:

Large Entity

Recommended Drawing for Patent Cover Sheet: Fig. 1

**Broadband Certified Mail**

## FIELD OF THE INVENTION

The present invention relates to communication between users in  
5 communication systems, and more particularly, to providing certified mail in a  
communication system including broadband communications.

## BACKGROUND OF THE INVENTION

Present day telephony networks, typically have end-to-end networks built around  
10 circuit switches, end offices, a toll network, tandem switches, and twisted wires. These  
networks are commonly referred to as a public switched telephone network (PSTN) or  
plain old telephone service (POTS). Due to bandwidth limitations of plain old telephone  
service (POTS), there is an inherent inability to efficiently integrate multiple types of  
media such as telephony, data communication for personal computers (PC), and  
15 television (TV) broadcasts. Further, the type of customer services and feature/function  
capability that may be implemented in a PSTN is somewhat limited relative to a  
broadband communication system. Accordingly, new broadband architectures are  
developing which transmits voice, data, and multimedia (video and audio)  
communications using, for example, communication information packets. These  
20 communication packets may be constructed in one or more packet protocols such as  
Internet Protocol (IP) or Asynchronous Transfer Mode (ATM). These new  
architectures gives rise to a new array of user services and capabilities not previously  
available with PSTN. One such new service and system capability of a packet based

broadband communication system is provided by the present application for certified mail.

Present PSTN voice mail systems do not readily provide a method that enables a caller to prove that they have left a voice mail or multimedia mail message for the called party, or for proving the content of that voice mail or multimedia mail, i.e., certified mail. Further, present PSTNs voice mail systems do not automatically include the digital representation of the message left that would enable electronic certification of a broadband communication mail message. The present PSTN infrastructure will not support certified mail. However, with the development of packet based broadband communication systems, certified voice and multimedia mail is possible to implement. Certified voice and multimedia mail represents a value to consumers as a means to enable a calling party to prove that they left a message for a called party on the called parties voice and/or multimedia mail system and establish the content of that message.

## SUMMARY OF THE INVENTION

The present invention provides a system and method for providing certified mail messages in a broadband communication system which uses packetized information. According to the invention, a broadband communication system user may be provisioned for certified voice and/or multimedia mail by registering with a certified mail service provider and thereby receiving certification including a certificate. The registration process may include the system user's broadband equipment providing a cryptographic public key to the service provider. In one variation, the system user's customer premises equipment and cryptography software will generate a private key (used to electronically

sign messages) and a public key (used to verify the electronic signature) for the user. In this case, the system user controls the private key and keeps it secret. In another variation, a service provider / certifying authority may provide the system user a unique public key and private key. In either case, the service provider / certifying authority issues a digital certificate certifying authenticity of the system user's identity and public key. The certificate may include, for example, the user's name and the user's public key, and is signed with the public key of the service provider / certifying authority. Further, the Certifying Authority may choose to include other information in the certificate, such as an expiration time, and the organization that the individual belongs to. The public key of the service provider / certifying authority may be well known so the user and a caller requesting certified mail may open the certificate. For example, it could be built into the customer premises equipment (CPE) of both parties to the call.

Once the broadband communication system user has registered with a service provider for certified voice mail and/or multimedia mail and received the certificate, their CPE, for example a broadband telephone interface (BTI), will be capable of offering certified voice and multimedia mail to a calling party. When a caller communicates with a system user that is registered for certified mail, by for example making a call, he may be given the option of leaving regular voice or multimedia mail or certified voice or multimedia mail. If the certified mail option is active and selected, then the caller and/or the called system user's CPE keeps track of the information packets (e.g. IP voice packets) used in the call. The called system user's CPE may then digitally sign the bits in the communication packets with a cryptographic electronic signature and return the signed message to the calling party, along with the system user's certificate obtained

from the service provider / certifying authority during registration. The calling party may then use its copy of the message, a copy of the message signed with the called parties electronic signature, and the certificate, to prove to anyone in possession of the service provider's public key, that he left the particular voice mail or multimedia mail message for the called party. The service provider / certifying authority may be notified and charge a fee each time the certified mail feature is utilized. Therefore, the caller can undeniably prove that the call happened and that the content of the message left was what he claims it to be.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 shows a schematic representation of a broadband network (e.g., broadband IP based network) in accordance with a preferred embodiment of aspects of the present invention.

Fig. 2 shows an information flow diagram for registration of a system user according to a preferred embodiment of the present invention.

Fig. 3 shows an information flow diagram of broadcasting a system user's public key according to a preferred embodiment of the present invention.

Fig. 4 shows an information flow diagram of certifying a voice mail message according to a preferred embodiment of the present invention.

Fig. 5 shows an information flow diagram of dispute resolution of a certified voice mail message according to a preferred embodiment of the present invention.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Certified mail according to the present invention serves purposes similar to “certified mail” offered by the United States Postal Service or any other postal service in that it provides a mechanism by which a person can prove that they had a particular communication with another person. However, the present invention extends the idea of certified mail to all types of electronic communications performed on a broadband communication system. For example, some preferred embodiments of the present invention are directed to certified voice mail and certified multimedia (video and audio) mail.

In general, the present invention provides a mechanism for callers to provide proof that they left a message for a particular party which that party cannot deny. The proof covers the content of the message as well as the fact that the communication was made. As packetized information traffic including, for example, voice and multimedia traffic, begins to be carried on broadband communication systems in digital form as packets, e.g., IP voice or multimedia packets, the number of services and features that can be offered increases. The present invention, referred to herein as broadband communication certified mail, is an example of such a service. Although the following preferred embodiments are directed particularly to certified voice mail, one skilled in the art will recognize that the invention is generally applicable to certifying multimedia mail including voice, video, and/or text messages communicated via a broadband communication system.

To achieve certified mail messages the present invention uses cryptography as a method of authenticating the identity of the recipient of the message and the contents of the message. A system user may subscribe to a service provider /certifying authority

and select a public key which will be use in certifying received voice or multimedia messages. This public key and a system user's related private key may be generated using cryptography software, for example, Pretty Good Privacy (PGP) or S/MIME. Although, the invention is not limited to these particular software packages. The system

5 user may provide the service provider / certifying authority with its public key at the time they subscribe for certified mail service. Alternatively, the service provider / certifying authority may generate and provide the user with a public key and a private key for use in the certification process. In either case, the private key is used to electronically sign any certified mail message which the system user receives and the public key is used to

10 electronically verify the electronic signature. The system user's identification (e.g., name) and public key may be included in a certificate generated by the service provider / certifying authority which is electronically signed using the service provider / certifying authority's public key. When a certified mail message is created, an electronically signed copy of the certified mail message and a copy of the certificate are sent to the party who

15 wishes to leave a certified mail message. The electronically signed message and the certificate may be subsequently used to undeniably prove that the party actually left the message and its contents with the person whom they claim to have left the message.

One preferred embodiment of a broadband communication system architecture in which the present invention may be implemented is illustrated in Figure 1. Although

20 the invention will be describe herein using the broadband communication system illustrated in Figure 1, it is understood that the invention may be implemented in any number of different broadband communication systems or variations of the broadband communication system illustrated in Figure 1. Some other possible broadband



communication system architectures in which the present invention may be implemented include those shown in, for example, U.S. Patent Application Serial No. 09/475,661 and U.S. Patent Application Serial No. 09/475,294 filed December 30, 1999, hereby incorporated by reference for all purposes.

5           As illustrated in Figure 1, the broadband communication system may include plurality of customer premise equipment (CPE) 110 and 120 used to interface with a broadband communication system, for example, Internet / broadband network 130. The CPEs 110 and 120 may include, for example, a cable modem (CM) 111 and 121 coupled to the Internet / Broadband Network 130 via a communication interface 115 and 125, 10       respectively. The communication interfaces 115 and 125 may be, for example, a coaxial cable, optical fiber, radio waves, etc, as long as it can handle broadband communications. Further, the CPEs 110 and 120 may include a personal computer (PC) 114 and 124, a broadband telephone interface (BTI) 112 and 122, and a telephone, 113 and 123. The cable modem 111 (or 121) and the broadband telephone interface 112 (or 122), may be 15       separate or integral in a single box such as a broadband residential gateway (BRG), and may further include a television interface. Likewise, the CM 111 (or 121) and/or BTI 112 (or 122) may be included in the PC 114 (or 124).

          The CPE 110 and 120 may further include a means for generating cryptographic keys such as cryptography software, for example, Pretty Good Privacy (PGP). The 20       means for generating cryptographic keys may be contained in any of the CPE 110 and 120, for example in the PC 114 and 124 or in the BTI 112 and 122. Further, the means for generating cryptographic key may include both hardware and software or may reside somewhere else in the broadband communication system. In any case, the cryptographic

keys may include both private and public keys and will provide electronic signature and verification means for certified mail. The private key may be a first algorithm that encodes the voice mail or multimedia mail message and the public key may be a second algorithm, related to the first algorithm, that decodes the voice mail or multimedia mail message so that the original message can be recaptured from the signed message.

The Internet / broadband network 130 may include a plurality of cable modem termination systems (CMTS) 131 and 132 to couple to the plurality of cable modems (e.g., CMs 111 and 121) coupled to the broadband communication system and one or more gate controllers 133 to coordinate communication traffic throughout the broadband system. The Internet / broadband network 130 may be coupled to a PSTN 160 via a gateway (GW) 165. Further, the broadband communication system may include a service provider / certifying authority 140 coupled to the Internet / broadband network 130 which provides the certified mail feature according to the present invention. The service provider / certifying agent 140 may include a server and appropriate software to operate the certified mail feature of the present invention, and may be located anywhere in the broadband communication system. The service provider / certifying agent 140 may include a means for placing an electronic signature on a certificate that certifies a subscriber's identity and public key, for example cryptography software such as PGP. Finally, the broadband communication system may include a judging authority 150 coupled to the Internet / broadband network 130 which may provide a forum for validating the authenticity of a certified mail message according to the present invention. The judging authority 150 may include a server and appropriate software to operate the certified mail feature of the present invention, and may be located anywhere in the

broadband communication system.

Any broadband communication system user / subscriber who wants to provide certified voice mail or multimedia mail to callers may register or subscribe for the service with the service provider / certifying authority 140. Referring to Figure 2, in a first  
5 embodiment the system user / subscriber 205 enters into a registration process in which the user provides credentials and a cryptographic public key (215) to the service provider / certifying authority 140. The credentials may include the users identity (e.g., name), directory number, address (geographical and/or system address (e.g. IP address)), etc., so that the service provider / certifying authority 140 may issue a certificate (220) which  
10 properly identifies the system user / subscriber 205. As indicated in the figures, the system user / subscriber may send their credentials and public key stored on their BTI 112 or PC 114 using, for example, the PC 114 or telephone 113, transmitted via the Internet / broadband network 130, to the service provider / certifying authority 140. The system user / subscriber 205 may generate, store, and control the private key and keep  
15 it secret using the CPE 110. The service provider / certifying authority 140 issues a digital certificate 220 which may include the system user / subscriber's 205 credentials and public key, and is electronically signed by the service provider / certifying authority 140 public key. The service provider 140 may also provisions the subscribers 205 CPE 110 to enable use of the certified mail feature. This provisioning may be performed  
20 when the system user subscribes for service. For example, the service provider / certifying authority 140 may, for example, separately transmit software that enables the subscriber's CPE 110 to operate the certified voice mail and multimedia mail message feature. This software may include cryptography software. Alternatively, the certificate

220 may include a program that automatically upon receipt enables the CPE 110 to operate the certified mail feature or the service provider 140.

In a further embodiment of the invention, the public key of the service provider / certifying authority 140 may be well known to other system users so that the various recipients of the certificate can open the certificate and verify its contents. For example, it could be built into the subscriber's customer premises equipment (CPE). Alternatively, the public key of the service provider / certifying authority 140 may be sent to the various system users upon request.

The system user / subscriber 205 then may use his CPE 110 to publish his certified mail public key issue by the service provider / certifying authority 140 so that the rest of the world, e.g., Internet / broadband network subscribers, knows his public key and can verify a certified mail message left for the system user / subscriber 205. As illustrated in Figure 3, the system user / subscriber 205 broadcasts his certified mail public key to the rest of the world (310), e.g., Internet / broadband network subscribers. This broadcast may occur in advance of the creation of a certified mail message. Alternatively, the system user / subscriber 205 may transmit his public key at the time a certified mail message is sent and/or at the time they subscribe for the certified mail feature.

Once the broadband system user has registered with a certified mail service provider and has received his certification (and if necessary software), the system user may activate or deactivate the certified voice mail and multimedia mail message feature by, for example, entering a particular code into the telephone 113 or selecting an icon on the PC 114. If the certified mail feature is activated then a telephone caller or a

multimedia caller will be provided the option of leaving a certified mail message. One example of an embodiment illustrating the operation of certified voice mail is described below. However, one skilled in the art would understand that the an alternative embodiment of the invention directed to certified multimedia mail is easily achieved by  
5 slight modification and the details of such a procedure are thus not included herein.

Referring now to Figure 4, the procedure for certified voice mail according to one embodiment of the invention is illustrated. First, a caller 410 places a call 401 to a callee 420 through respective CPEs (i.e., a CPE of a system user / subscriber who has registered for certified mail or who has the necessary cryptographic software) by dialing, for  
10 example, a telephone directory number or a system address. The call is carried over a broadband communication system using packetized information, for example, IP, such as the system illustrated in Figure 1. The call might be placed with phone 113 to phone 123 via the respective BTIs and CMs through the Internet / broadband network 130 or via multimedia PCs 114 and 124. Next, the callee's CPE 420 presents a menu of options  
15 to the caller 410 with a request to select an option 402. The options may include, for example, (1) leave a message (e.g., voice mail (VM)), (2) forward to another phone (FWD), and (3) leave a certified mail message (e.g., certified voice mail (CVM)) and may be a computer generated or voice recorded message. The select option message may be retained in the callee's CPE or within a centralized system in the Internet /broadband  
20 network 130. In any case, if the caller 410 chooses to leave a certified mail message by entering an appropriate response, e.g., selecting 3, his CPE sends a response indicating a selection of certified voice mail 403 to the callee's CPE 420 via the broadband communication system.

Then, the callee's CPE 420 indicates to go ahead by sending the caller 410 a prompt to begin 404, e.g., sending a beep sound. The caller 410 may then leave a voice message 405. The voice message, being transmitted in a packet based (e.g., IP) broadband communication system, will be digitized and packetized by the caller's CPE and sent to the callee 420 over, for example, Internet / broadband network 130. In one alternative, the caller's 410 CPE may retain a copy of the message packets being transmitted and recorded as a certified mail message. Next, the callee's CPE 420 receives the stream of digitized and packetized voice message packets (i.e., digital voice data) as the caller 420 leaves a voice message 405. Then the callee's CPE 420 may package the related message packets together so as to return them to the caller 420 as part of a return certified voice message 406. In one preferred embodiment, the related message packets may be combined and all headers removed so only voice message information data is left. Alternatively, each of the message packets may be electronically signed and sent to the caller's 410 CPE 110.

In any case, without converting the voice mail message contents to analog, the combined message packets may then be electronically signed using the callee's 420 private key, designated herein as  $\{M\}_{PV\ key}$ . The signed message  $\{M\}_{PV\ key}$  is returned to the caller 410, along with the certificate 220 from the service provider / certifying authority 140, as returned certified voice message 406. The signed message  $\{M\}_{PV\ key}$  and certificate 220 may be saved to memory in the caller's CPE 410 or may be transmitted to a central network service center for storage until needed if a dispute over whether the message was ever left with the callee 420 ever arises. Subsequently, the caller 410 may verify the certification 407 of the certificate 220.

To verify the certification the caller 410 would open the certificate 220 using the service provider / certifying authority's 140 public key and confirm that the callee's 420 credentials stored therein are correct and a public key for the callee 420 was included. Further, the caller 410 would verify the electronic signature of the coded message received by opening the message with the callee's 420 public key. If the resultant message matches the original message left for the callee 420, then the verification is complete and the caller 410 has successfully left a certified mail message for callee 420. Therefore, the caller 410 will have verified the certification from the service provider / certifying authority 140 and the callee's 420 signature on the message 408.

In another preferred embodiment, the service provider / certifying authority 140 may be notified by, for example a message from the callee's 420 CPE 110, and the service provider / certifying authority 140 may charge the callee 420 a fee. This fee for service may occur each time the certified mail feature is utilized, or there could be a subscription for service.

In one variation of the invention, the system may facilitate certified voice mail for a voice mail message left by a caller using an off network telephone, for example a POTS telephone or a cell phone originating from, for example, the PSTN 160. In this case, since the caller will not integrally connected with their own PC 114 or BTI 112 at their customer premises, the system will be constructed and operate so that the signed message packet and certificate are stored at a location which may be designated by the caller. For example, the caller may choose to store the signed message packet(s) and certificate transmitted by the callee's 420 CPE 120 at their own CPE 110, the service provider / certifying agent 140, at the judging authority 150, or at some other party

location on or off the network. The system may automatically determine that the call is originating from an off network telephone by determining that packets are originating from a bridging gateway (GW) 165 and prompt the caller to enter their desired certified mail storage destination by entering, for example, a system name or address, or selecting

5 from a menu of choices. The caller can enter the destination information by, for example, pressing the keypad on a POTS telephone or cell phone or by responding verbally and having a voice recognition system determine the caller's response. As long as the callee 420 is on a packet based network such as an IP network, at the gateway 165 from the PSTN 160 to the Internet/ broadband network, the call will be digitized and

10 packetized. When the voice packets reach the callee's 420 CPE 120, the callee's 420 CPE 120 may sign the digital voice data packets the same way as describe in the above embodiments. The difference in this embodiment is that the signed certified message packet(s) and certificate 220 must now reach an alternative destination, not the gateway 165, such as the caller's CPE 120, because the off network communication device, for

15 example a telephone, is not equipped to verify and store the certified mail information. Therefore, by the caller entering, for example, a code into the off network telephone indicating the alternative certified mail storage location, for example their BTI 112, the callee's 420 CPE 120 can send the signed message packet(s) and certificate 220 to the selected location after the call and message is completed. The callee's 420 CPE 120

20 could also use caller ID information to route the signed data to a known or predetermined destination previously entered into the system, thus eliminating the requirement that the user enter a code at the time a certified mail message is created.

If there is ever a dispute as to whether the caller 410 left the callee 420 a



particular voice mail message, the caller may a dispute resolution process by submitting the certified voice mail message  $\{M\}_{Pv\ key}$  and certificate to a judging authority 150 so that message authentication and content can be verified. Referring to Figure 5, the certified mail message dispute resolution process begins with the caller 410 sending a

5 complaint 501 including the signed message  $\{M\}_{Pv\ key}$  and certificate 220 from received from the callee 420 to a judging authority 150. This information may be transmitted to the judging authority 150 via the Internet / broadband network 130. The judging authority 150 may then send a public key query 502 to the service provider / certifying authority 140, asking for its public key. Next, the service provider / certifying authority

10 140 sends its public key 503 to the judging authority 150. However, if the judging authority 150 is a subscriber of the service provider / certifying authority 140, it may already have the service provider / certifying authority's 140 public key. In either case, then, the judging authority verifies the certificate 220 by opening the certificate using the service provider / certifying authority's 140 public key 503. Then, the judging authority

15 150 verifies the signed message  $\{M\}_{Pv\ key}$  by recovering the original message from the encoded message using the callee's 420 public key included in the certificate 220 (step 505). Next, the judging authority 150 issues his ruling based on the success or failure of the verification. If the digital representation of the decoded message matches the digital representation of the original message, than the judging authority 150 verifies the authenticity of the message and the identity of the recipient. The judging authority 150 may uses the same signing and verification software used by the caller 410 and the callee 420.

Although particular embodiments of the present invention have been shown and

described, it will be understood that it is not intended to limit the invention to the preferred embodiments and it will be obvious to those skilled in the art that various changes and modifications may be made without departing from the spirit and scope of the present invention. Thus, the invention is intended to cover alternatives, 5 modifications, and equivalents, which may be included within the spirit and scope of the invention as defined by the claims. For example, the present invention is applicable to any broadband communication system in which cryptography may be used to establish authentication and certification of mail messages transmitted in digital packet formats, such as asynchronous transfer mode (ATM) or Internet Protocol (IP) based broadband 10 communication systems. Further, the present invention may be used to certify all types of electronic mail including voice, text, and multimedia. In addition, the certified mail feature of the present invention may be implemented using software and/or hardware located anywhere within a broadband communication system, for example, in customer premises equipment (CPU) such as a PC, BTI, or BRG, in a service provider /certifying 15 authority server, in a judging authority server, or in a central services server located anywhere within the broadband communication system.

All publications, patents, and patent applications cited herein are hereby incorporated by reference in their entirety for all purposes.

WHAT IS CLAIMED IS:

1 1. A method for certifying electronic voice or multimedia messages, comprising the  
2 steps of:

3 receiving a plurality of digitized information packets;

4 compiling said digitized information packets into a mail message; and

5 attaching an electronic signature to said mail message to indicate that a message  
6 recipient received said mail message.

1 2. The method according to claim 1, further comprising the steps of:

2 sending said mail message with said electronic signature to a calling party who  
3 sent said digitized information packets; and

4 sending a certificate to said calling party who sent said digitized information  
5 packets certifying the identity of said recipient who received said mail message.

1 3. The method according to claim 2, further comprising the steps of:

2 generating said certificate; and

3 sending said certificate from a certification provider to said message recipient.

1 4. The method according to claim 3, further comprising the steps of:

2            sending said mail message with said electronic signature and said certificate from  
3            said party who sent said digitized information packets to a judge; and  
4            judging the authenticity of said mail message.

1        5.        The method according to claim 4, further comprising the step of:  
2            verifying said certificate is authentic by using a cryptography key of said  
3            certification provider.

1        6.        The method according to claim 6, further comprising the step of:  
2            verifying said electronic signature is authentic by using cryptography key  
3            contained in said certification provider.

1        7.        The method according to claim 2, further comprising the step of:  
2            prompting said party who sent said digitized information packets to select an  
3            option including leaving a certified mail message.

1        8.        The method according to claim 7, further comprising the steps of:  
2            verifying said certificate by said party who sent said digitized information  
3            packets; and

4            verifying said electronic signature of said recipient by said party who sent said  
5   digitized information packets.

1            9.        The method according to claim 2, wherein said electronic signature is  
2   cryptography key of said recipient.

1   10.    A method for certifying electronic messages in a broadband communication  
2   system, comprising the steps of:

3            attaching an electronic signature including a cryptography key to a mail message  
4   to indicate that a recipient received said mail message;

5            sending said mail message with said electronic signature to a calling party who  
6   sent said digitized information packets; and

7            sending a certificate to said calling party who sent said digitized information  
8   packets certifying the identity of said recipient who received said mail message.

1   11.    A broadband communication system, comprising:

2            a customer premises equipment system that packages a plurality of digital  
3   communication information packets into a single mail message, adds a user electronic  
4   signature to said single mail message, and sends said single mail message along with a  
5   certificate to another location for certifying a message.

1 12. The system according to claim 11, further comprising:  
2 a certifying system that generates said certificate for certifying mail transmitted  
3 in the broadband communication system.

1 13. The system according to claim 12, further comprising:  
2 a judging system that determines the authenticity of said certificate and said  
3 certified mail.

1 14. The system according to claim 11, wherein said electronic signature is a  
2 cryptography key.

1 15. The system according to claim 14, wherein said another location is a caller's  
2 customer premises equipment system.

1 16. The system according to claim 14, wherein said another location is a system  
2 server.

1 17. The system according to claim 12, wherein said certifying system includes a  
2 server.

1 18. The system according to claim 13, wherein said judging system includes a server.

1 19. The system according to claim 11, wherein said single mail message is a voice  
2 mail message.

1 20. The system according to claim 11, wherein said single mail message is a  
2 multimedia mail message.

1 21. The system according to claim 11, wherein said plurality of digital  
2 communication information packets are generated during a communication session that  
3 originates from an off network communication device.

1 22. The system according to claim 1, wherein said plurality of digitized information  
2 packets are generated during a communication session that originates from an off  
3 network communication device.

## ABSTRACT

The present invention provides a system and method for providing certified voice and/or multimedia mail messages in a broadband signed communication system which

5 uses packetized digital information. Cryptography is used to authenticate the saved message using a certificate of the originators identity and electronic signature. A broadband communication system user may be provisioned for certified voice and/or multimedia mail by registering with a certified mail service provider and thereby receiving certification. The registration process may include the system user's customer

10 premises equipment providing a cryptographic public key to the service provider. In response, the service provider issues a digital certificate certifying authenticity of the system user's identity and public key. Once the broadband communication system user has registered with a service provider for certified voice and/or multimedia mail and received the certificate, they may offer certified voice and multimedia mail to a calling

15 party. When a caller communicates with a system user that is registered for certified mail, by for example making a telephone or multimedia call, he may be given the option of leaving a certified voice mail or certified multimedia mail. The caller and the called system user's customer premises equipment may keep track of the information packets used in the call. The called system user's CPE may then electronically sign the bits in

20 the communication packets and return the message with an electronic signature of the called system user to the calling party, along with the system user's certificate obtained from the service provider / certifying authority during registration. The electronic signature is a cryptographic key of the called party. The calling party may then use its copy of the message, a copy of the message including the electronic signature received



25 from the called party, and the certificate, to undeniably prove to anyone in possession of the service provider's public key, that he left the voice or multimedia mail message for the called party. Further, the caller may prove that the call happened and that the message left was what he claims it to be by submitting this information to a judging authority.

30




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5

IN THE UNITED STATES  
PATENT AND TRADEMARK OFFICE

Declaration and Power of Attorney

As the below named inventors, I hereby declare that:

My residence, post office address and citizenship are as stated below next to our names.

I believe I am the original, first and joint inventors of the subject matter which is claimed and for which a patent is sought on the invention entitled **Broadband Certified Mail** the specification of which is attached hereto.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by an amendment, if any, specifically referred to in this oath or declaration.

I acknowledge the duty to disclose all information known to us which is material to patentability as defined in Title 37, Code of Federal Regulations, 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, 119 of any foreign application(s) for patent or inventors certificate listed below and have also identified below any foreign application for patent or inventors certificate having a filing date before that of the application on which priority is claimed:

None

I hereby claim the benefit under Title 35, United States Code, 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, 112, I acknowledge the duty to disclose all information known to us to be material to patentability as defined in Title 37, Code of Federal Regulations, 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

None

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be

true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I hereby appoint the following attorneys with full power of substitution and revocation, to prosecute said application, to make alterations and amendments therein, to receive the patent, and to transact all business in the Patent and Trademark Office connected therewith:

Samuel H. Dworetzky	(Reg. No. 27873)
Thomas A. Restaino	(Reg. No. 33444)
Michele L. Conover	(Reg. No. 34962)
Benjamin S. Lee	(Reg. No. 42787)
Robert B. Levy	(Reg. No. 28234)
Alfred G. Steinmetz	(Reg. No. 22971)
Cedric G. DeLaCruz	(Reg. No. 36498)
Rohini K. Garg	(Reg. No. 45272)
Susan E. McHale	(Reg. No. 35948)

I also appoint Thomas H. Jackson (Reg. No. 29808) and Kevin Alan Wolff (Reg. No. 42233) of Banner & Witcoff as associate attorneys, with full power to prosecute said application, to make alterations and amendments therein, and to transact all business in the U.S. Patent and Trademark Office connected therewith.

Please address all correspondence to Mr. S. H. Dworetzky, AT&T Corp., P.O. Box 4110, Middletown, New Jersey 07748. Telephone calls should be made to Thomas H. Jackson at 202-508-9119.

Full name of the sole inventor: Aviel D. Rubin

Inventor's signature  Date 4/6/00

Residence: W. Caldwell, Essex County, New Jersey

Citizenship: United States of America

Post Office Address: 1 Rubino Road, W. Caldwell, New Jersey 07006